

Product description	M12-B cable connector, Contacts: 4, not shielded, moulded on cable, IP68, UL listed, PUR black, 4 x 0.34 mm²
Area	M12-B series 766
Order number	77 4429 0000 50004-0500

Illustration	Scale drawing	Contact arrangement															
		<table border="1" style="margin: 10px;"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2,50</td> <td>0,00</td> </tr> <tr> <td>2</td> <td>0,00</td> <td>2,50</td> </tr> <tr> <td>3</td> <td>-2,50</td> <td>0,00</td> </tr> <tr> <td>4</td> <td>0,00</td> <td>-2,50</td> </tr> </tbody> </table> <p> 1 brown 2 white 3 blue 4 black </p>		X	Y	1	2,50	0,00	2	0,00	2,50	3	-2,50	0,00	4	0,00	-2,50
	X	Y															
1	2,50	0,00															
2	0,00	2,50															
3	-2,50	0,00															
4	0,00	-2,50															

Technical data

General values

Connector design	cable connector
Connector locking system	screw
Termination	moulded on cable
Wire gauge (mm)	0.34 mm ²
Wire gauge (AWG)	22
Upper limit temperature	90 °C
Lower limit temperature	- 25 °C
Customs tariff number	85444290

Cable data

Cable length	5 m
Sheath material	PUR
Single-lead insulation	PP
Single-lead structure	43 x 0.01 mm
Cable diameter	4.7 mm
Conductor resistance	60Ω/Km
Temperature range, moving cable, °C from	- 25 °C
Temperature range, moving cable, °C to	90 °C (UL 80 °C)
Temperature range, fixed cable, °C from	-50°C
Temperature range, fixed cable, °C to	90 °C (UL 80 °C)
Bending radius, fixed cable	24 mm
Bending radius, moving cable	47 mm
Approval 1	UL listed
UL style 1	AWM20549

Electrical values

Rated current (40 °C)	4 A
Rated voltage	250 V
Rated impulse voltage	2500 V
Pollution degree	3
Overvoltage category	II
Insulating material group	II
Insulation resistance	> 10 ⁸ Ω
EMC compliance	not shielded
Degree of protection	IP68
Mechanical operation	> 100 Mating cycles

Material

Contact material	CuZn (brass)
Contact plating	Au (gold)
Contact body material	PUR
Housing material	PUR

Product description	M12-B cable connector, Contacts: 4, not shielded, moulded on cable, IP68, UL listed, PUR black, 4 x 0.34 mm²
Area	M12-B series 766
Order number	77 4429 0000 50004-0500

Security notices

The connector must not be connected or separated under load. Non-observance and incorrect use can result in personal injury.

The connectors are designed for use in plant, control system and electrical equipment. The end user is responsible for checking whether the connectors are suitable for use in other applications.

Connectors with degree of protection IP 67 and IP 68 are not suitable for use under water. When used outdoors, the connectors must be separately protected against corrosion. For further information about IP degrees of protection refer to 'Technical support' in the Download Centre.

To lock the cable connector to the equipment connector, the threaded ring is tightened until it is 'finger-tight' (approx. 50 cNm).